

drop arm cassetted awning technical guide

- Fully cassetted robust drop arm commercial awning.
- Robust nature makes it suitable in exposed area.
- Opening can be manual winding or motorised. Above 4mtr width requires motorised operation.
- Canopy is Orchestra acrylic material 300g/m² with CLEANGARD treatment, which is anti staining, rot proof, water resistant and oil repellent. The material can withstand 350mm column of water (Schmerber test) and has good colour fastness to UV light (7/8 ISO 105-B04/94). The material is available in various colours.
- Awnings up to 2mtr projection are to EN 13561 wind resistance to class 2-Beaufort 5 (38km/h).
- The cassette comes in standard colours white (RAL9010) and brown (RAL8019) other RAL colours are available on request.
- Fully automatic arm lift.
- Branding is available on the valance and main body.
- Wall mounted lighting and heating can be fitted.



Width mm	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500	6000
Straight Projection											
1400	1.4	2.1	2.8	3.5	4.2	4.9	5.6	6.3	7.0	7.7	8.4
1700	1.7	2.5	3.4	4.2	5.1	5.9	6.8	7.6	8.5	9.3	10.2
2000	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0

■ Highlighted numbers show area of coverage in m².

inn-fresco
OUTDOOR SOLUTIONS

Newmarket Approach, Leeds, LS9 0RJ Tel: 0870 80 30 199
Fax: 0113 249 2228 www.inn-fresco.co.uk